

New Artisan™ Portable pH Meter

New PH2000 portable pH meter offers convenience and accuracy in a small easy-to-use instrument. The Automatic Temperature Compensation (ATC) assures that all readings are corrected to compensate for the effect of temperature. Adjust ATC manually or automatically with optional external thermistor temperature sensor. Datalog pH changes with RS-232 output and optional Windows software. Backlit display is easy to read in dark areas.

Calibrate this meter for 1-3 points with a wide range of general purpose electrodes. Use mV display for ion-selective electrodes. Protective ABS case, battery, pH buffer solutions and manual included. Low battery indicator. ABS housing. One year warranty.

**Dual Display
pH & Temp!**



Use the Artisan™ PH2000 portable meter with a wide range of pH and Ion-selective probes.

SPECIAL FEATURES

- Dual Display pH/mV & Temperature
- ATC - Automatic Temperature Compensation
- Calibrate easily with 1-3 points
- RS-232 Output
- Rugged ABS storage case



APPLICATIONS

- Laboratory Testing
- Water Treatment
- Wastewater Treatment
- Pools
- Plant Maintenance
- Spas
- Aquariums
- Car Washes

SPECIFICATIONS

	pH	mV
Measurement Range:	0.00 to 14.00	-499 to +499
Resolution:	0.01 pH units	0.1 (±0.1 to 195.0) 1 (±195 to 499)
Accuracy:	±0.02 pH units	0.2 (±0.1 to 195.0) 2 (±195 to 499)
Temp. Compensation:	-5 to 80°C (23 to 176°F)(thermistor)	
Input Impedance:	10 ¹² ohms	
Built-in Slope Control		
Operating Temp.:	0 to 50°C (32 to 122°F)	
Operating Humidity:	0 to 80% RH, non-condensing	
Storage Temp.:	-20 to 60°C (-4 to 140°F)	
Serial Output:	RS-232; 2400 baud, 1 stop, 8 data bits TXXX.XC, XX.XpH, TXXX.XF, XX.XmV	
Auto shutoff:	after 20 min of non-operation (disable features available)	
Power:	9 Volt battery (100 hrs life typ.)	
Dimensions:	180 x 72 x 30 mm (meter only) (L x W x D) (7.1 x 2.8 x 1.2 in.)	
(case dim.)	292 x 192 x 57 (11.5 x 7.6 x 2.3 in.)	
Weight (meter):	200 g (7 oz)	
Shipping Wt:	0.9 kg (2 lb)	

PH2000 Ordering Information

Part No.	Description
PH2000.001	pH meter, ABS case & battery.
PH2000.900	pH Sensor, combination, epoxy.
HH1000.950	Windows® software with PC cable.
PH0300.600	Calibration Solution, pH 4.01, qt.
PH0300.610	Calibration Solution, pH 7, qt.
PH0300.620	Calibration Solution, pH 10, qt.

APT logo, Artisan™-TM Advanced Product Technology, LLC Windows-Reg TM Microsoft Corp. © Copyright 2002 APT Instruments. Specifications subject to change.

For more information contact:

iProcessmart.com

USA

925.706.2583 Tel

925.706.2583 Fax

www.JdfcWgga Ufh.com

sales@JdfcWgga Ufh.com