

CORROSIVE SOLUTION, MEDIUM WEIGHT OIL, HEAT TRANSFER FLUIDS AND LIQUID PARAFFIN HEATING – 14 watts/sq. in.

4" 150 LB ASA STAINLESS STEEL FLANGE				CATALOG NUMBERS	
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 22	FIG. 23
4	240	1	13 ³ / ₈	H4A-6-0206-M1	H4A-6-0206-M7
5	240	1	16	H4A-6-0208-M1	H4A-6-0208-M7
6	240	1	18 ³ / ₈	H4A-6-0209-M1	H4A-6-0209-M7
8	240	1	22 ⁷ / ₈	H4A-6-0210-M1	H4A-6-0210-M7
	480			H4A-6-0211-M1	H4A-6-0211-M7
10	240	1	27 ⁷ / ₈	H4A-6-0212-M1	H4A-6-0212-M7
	480			H4A-6-0213-M1	H4A-6-0213-M7
12	240	1	32 ⁷ / ₈	H4A-6-0214-M1	H4A-6-0214-M7
	480			H4A-6-0215-M1	H4A-6-0215-M7
16	240	1	42 ³ / ₈	H4A-6-0216-M1	H4A-6-0216-M7
	480			H4A-6-0217-M1	H4A-6-0217-M7
20	240	1	51 ⁷ / ₈	H4A-6-0218-M1	H4A-6-0218-M7
	480			H4A-6-0219-M1	H4A-6-0119-M7

6" 150 LB ASASTAINLESS STEEL FLANGE				CATALOG NUMBERS		
KILOWATTS	VOLTS 3 PHASE	NUMBER OF CIRCUITS	B IMMERSION LENGTH	FIG. 24	FIG. 25	FIG. 26
10	240	5	13 ³ / ₈	H6A-15-0406-M1	H6A-15-0406-M5	H6A-15-0406-M6
12.5	240	5	16	H6A-15-0407-M1	H6A-15-0407-M5	H6A-15-0407-M6
15	240	5	18 ³ / ₈	H6A-15-0408-M1	H6A-15-0408-M5	H6A-15-0408-M6
20	240	5	22 ⁷ / ₈	H6A-15-0409-M1	H6A-15-0409-M5	H6A-15-0409-M6
	480			H6A-15-0410-M1	H6A-15-0410-M5	H6A-15-0410-M6
25	240	5	27 ⁷ / ₈	H6A-15-0411-M1	H6A-15-0411-M5	H6A-15-0411-M6
	480			H6A-15-0412-M1	H6A-15-0412-M5	H6A-15-0412-M6
30	240	5	32 ⁷ / ₈	H6A-15-0413-M1	H6A-15-0413-M5	H6A-15-0413-M6
	480			H6A-15-0414-M1	H6A-15-0414-M5	H6A-15-0414-M6
40	240	5	42 ³ / ₈	H6A-15-0415-M1	H6A-15-0415-M5	H6A-15-0415-M6
	480			H6A-15-0416-M1	H6A-15-0416-M5	H6A-15-0416-M6
50	240	5	51 ⁷ / ₈	H6A-15-0417-M1	H6A-15-0417-M5	H6A-15-0417-M6
	480			H6A-15-0418-M1	H6A-15-0418-M5	H6A-15-0418-M6