

PROVIDES **CLEAN, REGULATED AIR** TO YOUR APPLICATIONS!



RT250-G

- ✓ ¼" Filter with adjustable 0-120 PSI regulator
- ✓ Filter/Regulator with glass face chrome gauge
- ✓ Low Pressure Drop
- ✓ Can be wall mounted
- ✓ Low cost, high efficiency design
- ✓ Semi-automatic drain with manual override
- ✓ Filters to 5 micron
- ✓ Maximum pressure is 230 PSI
- ✓ Temperature range from 41°F to 122°F



RT500-G

- ✓ ½" Filter with adjustable 0-120 PSI regulator
- ✓ Filter/Regulator with glass face chrome gauge
- ✓ Low Pressure Drop
- ✓ Can be wall mounted
- ✓ Low cost, high efficiency design
- ✓ Semi-automatic drain with manual override
- ✓ Filters to 5 micron
- ✓ Maximum pressure is 180 PSI
- ✓ Temperature range from 41°F to 122°F

PROVIDES CLEAN AIR AT A
Low Cost!



RT250

- ✓ ¼" Air Filter
- ✓ 5 micron replacable filter element
- ✓ Low Pressure Drop
- ✓ Can be wall mounted
- ✓ Lightweight, High efficiency design is durable and rugged
- ✓ Semi-automatic drain with manual override
- ✓ Maximum pressure is 230 PSI
- ✓ Temperature range from 41°F to 122°F



RT500

- ✓ ½" Air Filter
- ✓ 5 micron replacable filter element
- ✓ Low Pressure Drop
- ✓ Can be wall mounted
- ✓ Lightweight, High efficiency design is durable and rugged
- ✓ Semi-automatic drain with manual override
- ✓ Maximum pressure is 180 PSI
- ✓ Temperature range from 41°F to 122°F