



SPECIFICATIONS

MODEL	UPF-2000	UPF-3000	UPF-4000	UPF-5000
PORT SIZE (NPT)	1/8", 1/4"	1/4", 3/8"	3/8", 1/2"	3/4", 1"
MAX SUPPLY PRESSURE	231 PSI (1.5 MPa)			
MAX OPERATING PRESSURE	150 PSI (990 Kpa)			
AMBIENT & MEDIA TEMP	40 ~ 140°F (5 ~ 60°C)			
FILTRATION	Standard: 10μm			
BOWL CAPACITY (OZ)	0.9	2.0	6.0	11
BOWL MATERIAL	Polycarbonate			
WEIGHT LBS (kgf)	0.42 (0.19)	0.64 (0.29)	1.21 (0.55)	1.85 (0.84)


ACCESSORIES (OPTIONAL)

	Part Number			
NAME	UPF-2000	UPF-3000	UPF-4000	UPF-5000
BRACKET	PF2000-43-6034	TAF3000-43-6004	TAF4000-08-6003	PC5000-08-6075
AUTO DRAIN (N·O)	*PF2000-01A-6039	TAF3000-01A-6008	TAF4000-01A-6009	PC5000-01A-6071

– Min Operating Pressure: 1kgf/cm² (15 PSI)

* Differential Pressure type

How TO ORDER



1 Air Filter

2 Body Size

20 : 1/4"

30 : 3/8"

40 : 1/2"

50 : 1"

3 Port Size (NPT)

01 : 1/8"

02 : 1/4"

03 : 3/8"

04 : 1/2"

06 : 3/4"

10 : 1"

4 Accessory

B : Bracket

D : Auto drain(N·O)

* UPF2000 : Differential Pressure type

5 Bowl Guard Option

(Series 2000, 3000 Only)

Blank : None(Standard Type)

C : Metal Bowl Guard

XC16 : Copper-free