

SPECIFICATIONS




MODEL	UPL-2000	UPL-3000	UPL-4000	UPL-5000
PORT SIZE (NPT)	1/8", 1/4"	1/4", 3/8"	3/8", 1/2"	3/4", 1"
MAX SUPPLY PRESSURE	231 PSI (1.5 MPa)			
MAX OPERATING PRESSURE	150 PSI (990 Kpa)			
MIN OPERATING FLOW SCFM(Nℓ/min)*	1/8: 0.53(15) 1/4: 1.06(30)	1/4: 1.06(30) 3/8: 1.41(40)	3/8: 1.41(40) 1/2: 1.77(50)	3/4: 4.23(120) 1: 7.79(220)
BOWL CAPACITY (OZ)	1.27	3.1	7.9	11
RECOMMENDED OIL	Turbine oil ISO VG32			
AMBIENT & MEDIA TEMP	40 ~ 140°F (5 ~ 60°C)			
BOWL MATERIAL	Polycarbonate			
WEIGHT LBS (kgf)	0.49 (0.22)	0.66 (0.30)	1.15 (0.52)	1.87 (0.84)

*Conditions: Supply pressure -70 PSI(5kgf/cm²). Number of drop-5 drops/min, ISOVG32, 68°F (20°C)

ACCESSORIES (OPTIONAL)

NAME	Part Number			
	UPL-2000	UPL-3000	UPL-4000	UPR-5000
BRACKET	PF2000-43-6034	TAF3000-43-6004	TAC4000-08-6003	PC5000-08-6075

HOW TO ORDER



1 Lubricator

2 Body Size (NPT)

20 : 1/4"
30 : 3/8"
40 : 1/2"
50 : 1"

3 Port Size (NPT)

01 : NPT 1/8"
02 : NPT 1/4"
03 : NPT 3/8"
04 : NPT 1/2"
06 : NPT 3/4"
10 : NPT 1"

4 Accessory

B : Bracket

5 Bowl Guard Option

(Series 2000, 3000 Only)
Blank : None(Standard Type)
C : Metal Bowl Guard
XC16 : Copper-free