

### SPECIFICATIONS




| MODEL                        | UPR-2000              | UPR-3000    | UPR-4000    | UPR-5000   |
|------------------------------|-----------------------|-------------|-------------|------------|
| PORT SIZE (NPT)              | 1/8", 1/4"            | 1/4", 3/8"  | 3/8", 1/2"  | 3/4", 1"   |
| MAX SUPPLY PRESSURE          | 231 PSI (1.5 MPa)     |             |             |            |
| MAX OPERATING PRESSURE       | 150 PSI (9.9KPa)      |             |             |            |
| REGULATING RANGE             | 7~125 PSI (50~850kpa) |             |             |            |
| PORT SIZE FOR PRESSURE GAUGE | NPT 1/8"              |             |             |            |
| AMBIENT & MEDIA TEMP         | 40 ~ 140°F (5 ~60°C)  |             |             |            |
| CONSTRUCTION/REGULATOR       | Relieving type        |             |             |            |
| WEIGHT LBS (kgf)             | 0.46 (0.21)           | 0.90 (0.14) | 1.85 (0.84) | 2.5 (1.14) |

### ACCESSORIES (OPTIONAL)

|          | Part Number    |                  |                 |                 |
|----------|----------------|------------------|-----------------|-----------------|
| NAME     | UPR-2000       | UPR-3000         | UPR-4000        | UPR-5000        |
| BACKET   | PC2000-43-6035 | TAR3000-43-6005  | TAC4000-09-6003 | TAC4000-09-6003 |
| Pressure | 150 PSI        | TAR4000-16A-6001 |                 |                 |

### How TO ORDER



1 Regulator

2 Body Size (NPT)

20 : 1/4"  
30 : 3/8"  
40 : 1/2"  
50 : 1"

3 Port Size (NPT)

01 : 1/8"  
02 : 1/4"  
03 : 3/8"  
04 : 1/2"  
06 : 3/4"  
10 : 1"

4 Accessory

B : Bracket  
G : Pressure gauge

5 Special Option

Blank : Standard type  
XC16 : Copper-free