

SPECIFICATIONS




| MODEL | UPW-2000 | UPW-3000 | UPW-4000 | UPW-5000 |
|------------------------------|---|-------------|-------------|------------|
| PORT SIZE (NPT) | 1/8", 1/4" | 1/4", 3/8" | 3/8", 1/2" | 3/4", 1" |
| MAX SUPPLY PRESSURE | 231 PSI (1.5 MPa) | | | |
| MAX OPERATING PRESSURE | 150 PSI (9.9kgf/cm ²) | | | |
| REGULATING RANGE | 7~125 PSI (0.5~8.5kgf/cm ²) | | | |
| PORT SIZE FOR PRESSURE GAUGE | NPT 1/8" | | | |
| AMBIENT & MEDIA TEMP | 40 ~ 140 °F (5 ~ 60 °C) | | | |
| FILTRATION | Standard: 10µm | | | |
| BOWL CAPACITY (OZ) | 0.9 | 1.2 | 2.7 | 4.8 |
| BOWL MATERIAL | Polycarbonate | | | |
| CONSTRUCTION/REGULATOR | Relieving type | | | |
| WEIGHT LBS (kgf) | 0.66 (0.3) | 1.23 (0.56) | 2.54 (1.15) | 3.11(1.41) |

ACCESSORIES (OPTIONAL)

| | Part Number | | | |
|----------------|------------------|------------------|------------------|-----------------|
| NAME | UPW-2000 | UPW-3000 | UPW-4000 | UPW-5000 |
| BRACKET | PR2000-43-6005 | TAR3000-43-6005 | TAC4000-09-6003 | TAC4000-09-6003 |
| PRESSURE GAUGE | TAR4000-16-6001 | | | |
| AUTO DRAIN | PF2000-01A-6039* | TAF3000-01A-6008 | TAF4000-01A-6009 | PF5000-01A-6071 |

-- Min. operating pressure:N•O-14.2PSI (Float type) *Differential Pressure type

HOW TO ORDER



1 Filter Regulator

2 Body Size (NPT)

- 20 : NPT 1/4"
- 30 : NPT 3/8"
- 40 : NPT 1/2"
- 50 : NPT 1"

3 Port Size (NPT)

- 01 : NPT 1/8"
- 02 : NPT 1/4"
- 03 : NPT 3/8"
- 04 : NPT 1/2"
- 06 : NPT 3/4"
- 10 : NPT 1"

4 Accessory

- B : Bracket
- D : Auto drain:Float type(N.O)
- ※ UPW2000 :
Differential Pressure type
- G : Pressure gauge

5 Bowl Guard Option

- (Series 2000, 3000 Only)
- Blank : None(Standard Type)
- C : Metal Bowl Guard
- XC16 : Copper-free