

# Particle counting in the palm of your hand

Model 227A/227B Handheld Airborne Particle Counters

### **FEATURES**

- AC or battery operation
- 0.3 micron at 0.1 cfm (227B)
- 0.5 micron at 0.1 cfm (227A)
- Counts 2 sizes simultaneously
- Stores data from 200 locations
- Labels data with location
- Internal rechargeable battery
- Weighs only 2.1 lbs (0.97 kg)
- Spreadsheet-compatible data files with Particle Vision<sup>™</sup> PortAll<sup>™</sup> software

## **APPLICATIONS**

- Monitor and verify cleanrooms
- Test filters in place
- Track down particle sources

 Monitor: LAF and biohazard benches Cleanroom laundries HVAC systems Computer rooms Food and beverage packaging Hospitals: Pharmacy and surgery Indoor Air Quality (IAQ) Aerospace Assembly Medical Device Assembly Automotive: Paint spray booths Filter performance



The Model 227 Portable Airborne Particle Counter offers the features and sensitivity of larger instruments and easy handheld operation. Weighing only two pounds, the Model 227 features a sensitivity of 0.3 micron (227B) or a sensitivity of 0.5 micron (227A), is fully self-contained, and uses reliable laser diode technology. It connects to a remote printer or computer, and can be part of a facility-monitoring system.

The Model 227 counts two sizes of particles simultaneously. Sample times can be set for up to 24 hours. Count data are stored in memory for easy transfer to a printer or computer. To make the most of its portability, the Model 227 features several counting modes for quick analysis of cleanroom conditions. The concentration mode gives a continuously updated approximation of the number of particles per cubic foot or per liter. The approximation is based on a user-selectable sample period of one to ten seconds. In the auto mode, it automatically takes a specified number of samples and stops, allowing unattended operation. The average mode calculates the average, minimum, and maximum count after a specified number of samples.

In beep mode, the Model 227 sounds a beep each time it counts a specified number of particles. This is useful for locating leaks in filters.

To protect your cleanroom, the Model 227 contains an exhaust filter. The pump and sensor are turned off when the battery charge drops below a safe operating level, maintaining power to preserve data stored in memory. The Met One Model 227: a handful of information.







# Model 227A/227B Handheld Particle Counters

SPECIFICATIONS	Size Channels (µm)	227A	ch I ch2	0.5 selectable—0.7, 1.0, 3.0, or 5.0	
		227B	ch I	0.3	
			ch2	selectable-0.5, 1.0, 3.0, or 5.0	
	Flow Rate	0.1 cfm (2.83 lpm)			
	Light Source		aser diode (30,000 hours mean time between failure) Mono-dispersed polystyrene spheres (NIST traceable) I-line LCD, 7 digits		
	Factory Calibration	•			
	Display				
	Outputs	RS232C/RS485 for computer or printer			
	Location Labels	100, appear on printout			
	Data Storage	200 samples, 1	uffer		
	Sample and Hold Times	I second to 24	I second to 24 hours		
	Count Alarms	I to 9,999,999 each channel			
	Concentration Mode	I second samples, I to IO samples averaged, display updated every second; displays counts/ft <sup>3</sup> or liter			
	Power	AC adapter or internal battery pack			
	Battery	Rechargeable NiMH			
	Battery Recharge Time	90% in 10 hours; 100% in 12 hours			
	Operating Time	8 hours continuous			
	Size	4" wide x 6.9" high x 2.3" deep (10.3 x 17.5 x 5.9 cm)			
	Weight	2.1 lbs (0.97 kg)			
	Environment	Operating	55 to 8	4°F (12 to 29°C),	
			20 to 9	5% relative humidity, non-condensing	
		Storage	-40 to	160°F (-40 to 70°C),	
		C C	up to 9	98% relative humidity, non-condensing	
	Accessories Included	Isokinetic Probe (direct mount); Purge Filter; Recharger Stand;			
		AC Adapter; Operator's Manual			
ORDERING GUIDE	When ordering, specify:				
	Basic Sensitivity	0.3 micron (227B) or 0.5 micron (227A)			

OPTIONAL ACCESSORIES Power (AC) Relative Humidity/Temperature Sensor High Pressure Diffuser Particle Vision™ PortAll Software Printer, external

Carrying/Shipping Case

0.3 micron (227B) or 0.5 micron (227A) AC adapters for 100 VAC, 115 VAC, or 230 VAC

**P**acific INSTRUMENTS

#### UNITED STATES

481 California Avenue Grants Pass, Oregon 97526 United States Tel 1 541 479 1248 Fax 1 541 479 3057 Toll Free 1 800 866 7889

### ENGLAND

Pegasus House Haddenham Business Park Haddenham Bucks HP17 8LL England, United Kingdom Tel 44 (0) 1844 299 336 Fax 44 (0) 1844 299 379 
 FRANCE

 100 rue Blaise Pascal

 ZI les Mardelles

 93605 Aulnay-sous-Bois Cedex

 France

 Tel
 33 (0) 1 58 03 05 00

 Fax
 33 (0) 1 48 66 46 66



Ostwall 30 Lüdinghausen D-59348 Germany Tel 49 (0) 25 91 30 91 Fax 49 (0) 25 91 50 14

Royco

 SCOTLAND

 CEL Enterprise Centre
 58 Cornton Road

 Stirling FK9 5AT
 Scotland, United Kingdom

 Tel
 44 (0) 1786 448 338

 Fax
 44 (0) 1786 448 711

HYT

Met One

CE

PN 705050-REV. 6/99