



2000 BTUH  
Indoor/Outdoor, NEMA Types 12, 4 & 4X Available

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge air conditioners will exceed environmental requirements in applications like *Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics.*



**Digital Temperature Controller**

- Programmable set point and temperature operating controls
- Visible Error and/or alarm messaging
- System status indication
- Password protection

**Active Condensate Management System**

- Complete elimination of condensate
- Eradicates condensate without corrosive contact with coils

**Unit Efficiency**

- Pressure operated blower control reduces power inrush and saves energy
- High efficient rotary compressor
- Fully insulated & sealed cabinet
- Temperature Control Valve to provide a broad temperature range while maintaining cooling capacity.

**Compressor Protection System**

- High & Low refrigerant cutouts with fault indication
- Compressor anti short cycle protection
- Compressor run capacitors reduce power inrush, save energy and increase compressor life

**Options:**

- External Alarm Capabilities
- Corrosive Environment Package
- High and Low Ambient Packages
- Dry Contact Remote Monitoring Options
- Integrated Enclosure Heater System
- Hazardous Environment Units available
- Cooling Capacity's of 1000 to 20,000 BTUH

*Get the Edge...Get Thermal Edge*



UL File # SA32252

| Model       | BTU/ Hour | Material             | Voltage/ Hz. | Running Amps | Max. Ambient Temperature | H x W x D          | Ship Weight Lbs. |
|-------------|-----------|----------------------|--------------|--------------|--------------------------|--------------------|------------------|
| NE020126-12 | 2000      | Powder coated steel  | 120V/1/60    | 3.76         | 131°F                    | 32" x 11.8" x 9.5" | 70               |
| NE020126-04 | 2000      | Powder coated steel  | 120V/1/60    | 3.76         | 131°F                    | 32" x 11.8" x 9.5" | 70               |
| NE020126-4X | 2000      | 304 or 316 Stainless | 120V/1/60    | 3.76         | 131°F                    | 32" x 11.8" x 9.5" | 70               |
| NE020486-12 | 2000      | Powder coated steel  | 480V/1/60    | 1.8          | 131°F                    | 38" x 11.8" x 9.5" | 110              |
| NE020486-04 | 2000      | Powder coated steel  | 480V/1/60    | 1.8          | 131°F                    | 38" x 11.8" x 9.5" | 110              |
| NE020486-4X | 2000      | 304 or 316 Stainless | 480V/1/60    | 1.8          | 131°F                    | 38" x 11.8" x 9.5" | 110              |

All information subject to change without notice